

5TH CATEGORY - HISTORIC RACING GROUP S APPROVED VEHICLE SPECIFICATION

This form details the approved specifications of individual vehicle models in the 5th Category Historic car group. To be issued with an Historic Log Book, cars need to comply with these specifications, the physical appearance shown in the illustrations and the general historic rules as detailed in the current Motorsport Australia Manual.

Make of Car:	Porsche	Model:	356	
			С	
			SC	
Period of Original Manufacture:	1963 – 1965			
Motorsport Australia Historic Group:	Sb			
Date of Issue of this Document:	30/6/2022			
NOTE	1972 and later models are not eligible for Group Sb due			
	to changed	specificatio	ons	





Update Log

30/6/2022	Document layout

Caliper make:

Caliper type: Material:

Adjustable bias:

Servo Fitted:

Comments:

Type:

Master cylinder make:

1.1. CHASSIS								
Description:	Unitary cons	Unitary construction						
Period of Manufacture:	1963 - 1965	1963 - 1965						
Manufacturer:	Porsche KG	Porsche KG						
Chassis Number From:	126101>>>							
Chassis Number location:	Floor of fror	Floor of front luggage compartment						
Material:	Steel							
Comments	None							
1.2. FRONT SUSPENSION								
Description:	Independen	it, trailir	ng parallel links					
Spring Medium:	Torsion bar							
Damper Type:	Telescopic			Adj	ustable:		Optional	
Anti-sway bar:	Fitted			Adj	ustable:		No	
Suspension adjustable:	Yes		Method:		orsion	bar	tension,	Camber,
				C	astor			
Comments:	Ride height	unrestr	icted					
1.3. REAR SUSPENSION								
Description:	Independen		ng arms					
Spring Medium:		Torsion bars						
Damper Type:	Telescopic	Telescopic			justable Optional			
Anti-sway bar:	No				justable: N/A			
Suspension adjustable:	Yes		Method:	T	Forsion bar tension			
Comments:	Ride height	unrestr	icted					
1.4. STEERING								
Туре:	Worm and r	nut		Ma	ke:		ZF	
Comments	None							
1.5. BRAKES								
			Front				Rear	
Туре:			Disc, solid			Disc, solid		
Dimensions:			275 mm x 10 mm 2		265 mm x 10 mm			
Material of drum/disc:			Cast iron			Cast iron		
No. cylinders/pots per wheel:			Two		Тwo			
Actuation:			Hydraulic		Hydraulic			

ATE

Cast iron

Single

No

Yes

ATE – Lockheed

Fittent of twin master cylinders permitted.

Servo may be rendered inoperative

2.1. ENGINE

Make:	Porsche		
Model:	616		
No. cylinders:	Four	Configuration:	Horizontal boxer
Cylinder Block-material:	Alloy	Two/Four Stroke:	Four
Bore – Original:	82.5 mm	Max allowed:	84.0 mm
Stroke – original:	74 mm	Max allowed:	74 mm
Capacity – original:	1582 cc	Max allowed:	1640 cc
Identifying marks:			-
Cooling method:	Air and Oil		
Comments:	None		

2.2. CYLINDER HEAD

Make:	Porsche	Porsche			
Material:	Alloy				
No. of valves/cylinder:	Two	Inlet:	One	Exhaust:	One
No. of ports total:	Eight	Inlet:	Four	Exhaust:	Four
No. of camshafts:	One	Location:	Crankcase	Drive:	Gear
Valve actuation:	Pushro	Pushrod and rockers			
Spark plugs/cylinder:	One	One			
Identifying marks:	N/A	N/A			
Comments:	None				

2.3. LUBRICATION

Method:	Wet sump		
Dry sump type:	N/A	Location:	N/A
Oil cooler standard:	Yes	Location:	Engine compartment
Comments:	Oil cooler p	ermitted	

2.4. IGNITION SYSTEM

Туре:	oints, coil and distributor		
Make:	Bosch		
Comments	None		

2.5. FUEL SYSTEM

Carburettor Make:	Solex	Model:	40 P11-4	
Carburettor Make:	Zenith	Model:	32NDIX	
Carburettor Number:	Two	·		
Fuel injection Make:	N/A	Туре:		
Supercharged:	No	Туре:	N/A	
Comments:	None			

SECTION 3 - TRANSMISSION

3.1. CLUTCH

Make:	Porsche
Туре:	Diaphragm
Diameter:	200 mm
No. of Plates:	One
Actuation:	Hydraulic
Comments:	None

3.2. TRANSMISSION

Туре:	Transaxle
Make:	Porsche
Model	
Gearbox location:	Rear of car
No. forward speeds:	Four
Gearchange type and location:	Floor remote
Case material:	Alloy
Identifying marks:	N/A
Comments:	Ratios free.

3.3. FINAL DRIVE

Make:	Porsche
Model:	
Туре:	Transaxle to rear wheels
Wheel drive method:	Rear
Ratios:	
Differential type:	Free
Comments:	Limited slip differential optional.

3.4. TRANSMISSION SHAFTS (EXPOSED)

Number:	Тwo		
Location:	Transaxle to rear wheels		
Description:	Halfshafts with twin CV joints		
Comments:	None		

3.5. WHEELS & TYRES

Wheel type - Original:	Pressed steel	Materia	- Original:	Steel	
Wheel type - Allowed:	Cast or disc	Materia	- Allowed:	Alloy	
				Steel	
Fixture method:	Studs and nuts	No. stud	s:	Four	
Wheel dia. & rim width	FRONT	FRONT		REAR	
Original:	4.5" x 15"		4.5″ x 15″		
Allowed	6" x 15'	6" x 15"		6" x 15"	
Tyre Section:					
Original:	5.6 x 15"			5.6 x 15″	
Allowed:	195/60 x 15"				
Aspect ratio - minimum:	60% minimum aspect ratio.				
Comments:	Refer approved tyre list.				

4.1. FUEL SYSTEM

Tank Location:	Front compartment	Capacity:	50 litres
Fuel pump, type:	Mechanical on engine.	Make:	VW
Comments:	Fuel pump/s free		

4.2. ELECTRICAL SYSTEM

Voltage:	Six	Alternator fitted:	Generator
Battery Location:	RHS engine compartment		
Comments:	Voltage may be changed to 12		

4.3. BODYWORK

Туре:	Fixed head Coup Roadster	e or	Material:	Steel
No. of seats:	Two		No. doors:	Two
Comments:	None			

4.4. DIMENSIONS

Track - Front:	1306 mm	Rear:	1272 mm
Wheelbase:	2108 mm	Overall length:	4013 mm
Dry weight:	935 kg		
Comments:	None		

4.5. SAFETY EQUIPMENT

Refer applicable Group Regulations

Appendix