

VEHICLE ELIGIBILITY

5th Category – Historic

EQUIPMENT STANDARDS AND GUIDELINES

MOTORCYCLE TYRES – GROUPS J, K AND L

| Modified Article | Date of Application | Date of Publication |
|------------------|---------------------|---------------------|
| | | |

Vehicle Eligibility

EQUIPMENT STANDARDS AND GUIDELINES

1.1 LIST OF PERMITTED MOTORCYCLE TYRES – GROUPS J, K AND L

A selected list of motorcycle tyres is permitted for use on Groups J, K and L cars provided they are fitted to the correct width and profile rims, and are operated within their specified Speed and Load Index ratings.

The tyre section profile shall be as per configuration (a) of the Tyre and Rim Association of Australia manual.

Aspect ratios shall comply with individual group requirements.

Tyre hardness shall generally not be lower than 68 Durometer cold (measured prior to use) and not lower than 15° (ambient).

Short-life or low-profile tyres will not be acceptable.

Historic period design tyres made with modern “sticky” compounds are unacceptable. Tread patterns shall be of a period historic style.

Additional tyres to those shown in the approved tyre list will be considered on application if they meet the above criteria.

| Size | Make | Model | Size | Speed Rating (mph) | Load Limit (lb) | Rim Width |
|------|-------------|----------------------|-------------|--------------------|-----------------|-----------------|
| 15” | DUNLOP | Qualifier K827 | 140/90-15 | H 130 | 740 | MT 2.7 - 3.5 |
| 16” | AVON | SM MKII | 5.00 S16 | S 113 | 716 | MT 3.0 - 3.5 |
| | | Roadrunner R2 | 130/90 H16 | H 130 | 760 | MT 2.5 - 3.5 |
| | CHEN SHIN | C199 | 510 H16 | H 130 | 720 | MT 3.0 - 3.5 |
| | METZLER | Block K | 325-16 | H 130 | 425 | MT 1.85- MT 2.5 |
| 17” | AVON | Roadrunner Universal | 130 190 H17 | H 130 | 695 | MT 2.5 - 3.5 |
| | BRIDGESTONE | RS-10 | 250-17 | S 113 | 290 | 1.35-1.6, WM1 |
| | | RS-10 | 325-17 | S 113 | 440 | MT 1.85 - 2.5 |
| | CHEN SHIN | C119 | 4.50/85-H17 | H 130 | 645 | 2.5 - 3.00 |
| | | C180 | 300-17 | S 113 | 385 | 1.6 - 2.15 |
| | | C180 | 325-17 | S 113 | 440 | MT 1.85 - 2.5 |
| C180 | | 350-17 | S 113 | 493 | 1.85 - 2.50 | |
| 18” | AVON | SM MKII | 4.00 S18 | S 113 | 617 | 2.15 - MT 3.00 |
| | BRIDGESTONE | RS10 | 250-18 | S 113 | 250 | 1.35 - 1.6 |
| | | RS10 | 325-18 | S 113 | 440 | MT1.85 - MT2.5 |

... continued

| Size | Make | Model | Size | Speed Rating (mph) | Load Limit (lb) | Rim Width |
|-----------------|-----------|-----------|---------------|--------------------|-----------------|---------------|
| 18" (cont'd) | CHEN SHIN | C199 | 3.50/3.75 H18 | H 130 | 493 | 1.85 - 2.50 |
| | | C199 | 4.10/4.25 H18 | H 130 | 551 | 2.15 - 3.00 |
| | | C199 | 4.25/4.60 H18 | H 130 | 617 | 2.50 - 3.00 |
| | | C199 | 4.50/4.85 H18 | H 130 | 645 | 2.50 - 3.00 |
| | | C180 | 300-18 | S 113 | 385 | 1.60 - 2.15 |
| | | C180 | 350-18 | S 113 | 493 | 1.85 - 2.50 |
| | | C180 | 400-18 | S 113 | 617 | 2.15 - MT3.00 |
| | | C180 | 450-18 | S 113 | 661 | 2.50 - 3.00 |
| | DUNLOP | K70 | 300-18 | S 113 | 360 | 1.60 - 2.15 |
| | | K70 | 350-18 | S 113 | 450 | 1.85 - 2.50 |
| | | K70 | 400-18 | S 113 | 570 | 2.15 - MT3.00 |
| | | K81 TT100 | 360-18 | H 130 | 460 | 1.60 - 2.50 |
| | | K81 TT100 | 410-18 | H 130 | 575 | 2.15 - 3.00 |
| | | K81 TT100 | 425-18 | H 130 | 595 | 2.50 - 3.00 |
| | | K181 | 100-900 V18 | H 130 + | 493 | 2.15 - 2.75 |
| | | K700 | 150/70 VR18 | | | |
| | METZLER | BLOCK K | 400-18 | P 33 | 620 | 2.15 - MT3.00 |
| | MICHELIN | M38 | 300-18 | S 113 | 360 | 1.60 - 2.15 |
| | | M38 | 350-18 | S 113 | 490 | 1.85 - 2.50 |
| | | M38 | 400-18 | S 113 | 623 | 2.15 - MT3.00 |
| | YOKOHAMA | 12200 | 140/70 VR18 | | | |