

5TH CATEGORY - HISTORIC RACING

GROUP S

APPROVED VEHICLE SPECIFICATION

This form details the approved specifications of individual vehicle models in the 5th Category Historic car group. To be issued with an Historic Log Book, cars need to comply with these specifications, the physical appearance shown in the illustrations and the general historic rules as detailed in the current Motorsport Australia Manual.

Make of Car:	Fiat	Model:	124 AC Sport Coupe
Period of Original Manufacture:	1967 – 1969		
Motorsport Australia Historic Group:	Sb		
Date of Issue of this Document:	30/6/2022		



## **Update Log**

30/6/2022	Document layout

#### **SECTION 1 - CHASSIS**

# 1.1. CHASSIS

Description:	Unitary chassis/body	
Period of Manufacture:	1967 – 1969	
Manufacturer:	Fiat	
Chassis Number From:	124 AC 000	
<b>Chassis Number location:</b>		
Material:	Mild steel	
Comments		

## 1.2. FRONT SUSPENSION

Description:	Independen	Independent front suspension – twin wishbones				
Spring Medium:	Coil	Coil				
Damper Type:	Tubular	Tubular Adjustable: No				
Anti-sway bar:	Yes	Yes		No		
Suspension adjustable:	No	No Method: N/A				
Comments:	Spring rates	Spring rates and ride height unrestricted				

## 1.3. REAR SUSPENSION

Description:	Rigid axle, ra	Rigid axle, radius arms and Panhard bar				
Spring Medium:	Coil	Coil				
Damper Type:	Tubular	Tubular Adjustable No				
Anti-sway bar:	Yes		Adjustable:	No		
Suspension adjustable:	No	No Method: N/A				
Comments:	Spring rates	Spring rates and ride height unrestricted				

# 1.4. STEERING

Type:	Worm and roller	Make:	Fiat
Comments	None		

### 1.5. BRAKES

	Front	Rear	
Type:	Disc	Disc	
Dimensions:	227 mm	227 mm	
Material of drum/disc:	Cast iron	Cast iron	
No. cylinders/pots per wheel:	One	One	
Actuation:	Hydraulic	Hydraulic	
Caliper make:	Fiat		
Caliper type:			
Material:	Alloy		
Master cylinder make:	Fiat		
Type:	Tandem		
Adjustable bias:	No		
Servo Fitted:	Yes (Master vacuum)		
Comments:	Rear brake pressure regulator fitted as standard		

#### **SECTION 2 - ENGINE**

### 2.1. ENGINE

Make:	Fiat	Fiat				
Model:	124 AC	124 AC				
No. cylinders:	Four	Configuration:	In line			
Cylinder Block-material:	Cast iron	Two/Four Stroke:	Four			
Bore - Original:	80.0 mm	Max allowed:	81.5 mm			
Stroke - original:	71.5 mm	Max allowed:	71.5 mm			
Capacity - original:	1438 сс	Max allowed:	1492 cc			
Identifying marks:	Block casting numbe	r 124 AC				
Cooling method:	Liquid					
Comments:	None		_			

### 2.2. CYLINDER HEAD

Make:	Fiat					
No. of valves/cylinder:	Two	Inlet:	One	Exhaust:	One	
No. of ports total:	Eight	Inlet:	Four	Exhaust:	Four	
No. of camshafts:	Two	Location:	Head	Drive:	Toothed belt	
Valve actuation:	Overhea	Overhead cam				
Spark plugs/cylinder:	One					
Identifying marks:	124 A or 124 B					
Comments:	None					

# 2.3. LUBRICATION

Method:	Wet sump	Oil tank location:	N/A
Dry sump pump type:	N/A	Location:	N/A
Oil cooler standard:	No	Location:	N/A
Comments:	none		

## 2.4. IGNITION SYSTEM

Туре:	Points, Coil and Distributor		
Make:	Marelli 5124B		
Comments	None		

### 2.5. FUEL SYSTEM

Carburettor Make:	Weber	Model:	34 DFH	
			34 DHS	
Carburettor Number:	One			
Size:				
Fuel injection Make:	N/A	Type:	N/A	
Supercharged:	No	Type:	N/A	
Comments:	Two Webe	rs allowed.		
	Bore size u	nrestricted		

#### **SECTION 3 - TRANSMISSION**

### 3.1. CLUTCH

Make:	Fiat
Type:	Diaphragm
Diameter:	200 mm
No. of Plates:	One
Actuation:	Mechanical (cable)
Comments:	None

### 3.2. TRANSMISSION

Type:	Four or five speed synchromesh
Make:	Fiat
Gearbox location:	Behind engine
No. forward speeds:	Four or Five
Gearchange type and location:	Floor remote
Case material:	Aluminium Alloy
Identifying marks:	
Comments:	Ratios free

### 3.3. FINAL DRIVE

Make:	Fiat	Model:	
Wheel drive:	Rear		
Ratios:	Various		
Differential type:	Hypoid bevel		
Comments:	Ratios free		
	Limited slip differential allowed		

# 3.4. TRANSMISSION SHAFTS (EXPOSED)

Number:	One
Location:	Tailshaft
Description:	Two piece with centre bearing
Comments:	

## 3.5. WHEELS & TYRES

Wheel type - Original:	Disc	Material - Original:	Steel	
Wheel type - Allowed:	Cast alloy	Material - Allowed:	Aluminium Alloy	
Fixture method:	Bolt on	No. studs:	Four	
Wheel dia. & rim width	FRONT		REAR	
Original:	5" x 13"	5" x 13"		
Allowed	6" x 13" 6" x 13"		6" x 13"	
Tyre Section:				
Original:	13" x 165 13" x 165		13" x 165	
Allowed:	13" x 185"		13" x 185"	
Aspect ratio - minimum:	60% minimum aspect ratio.			
Comments:	Refer approved tyre list.			
	Rim size and tyre size limited to combination that will fit under			
	standard wheel arch.			
	Alloy wheels type should be as shown.			

\_

#### **SECTION 4 GENERAL**

## 4.1. FUEL SYSTEM

Tank Location:	Under boot	Capacity:	45 litres
Fuel pump, type:	Mechanical	Make:	
Comments:	None		

## 4.2. ELECTRICAL SYSTEM

Voltage:	Twelve	Alternator fitted:	Alternator
Battery Location:	Right front corner of engine bay		
Comments:	None		

## 4.3. BODYWORK

Type:	Fixed head coupe	Material:	Steel
	(Sports coupe)		
No. of seats:	Four	No. doors:	Two
Comments:	None		

## 4.4. DIMENSIONS

Track - Front:	1346 mm	Rear:	1316 mm
Wheelbase:	2420 mm	Overall length:	4115 mm
Dry weight:	960 kg		
Comments:	None		

### 4.5. SAFETY EQUIPMENT

Refer applicable Group Regulations

# Appendix